



Material Properties and Dimensions



Description

Western Excelsior manufactures Aspen Excelsior Logs in addition to a full line of Rolled Erosion Control Products (RECPs). Aspen Excelsior Sediment Control Logs consist of a machine produced High Altitude Rocky Mountain Aspen Excelsior Matrix confined by a synthetic net to form a log of specific length and diameter. Aspen Excelsior Logs are designed to reduce hydraulic energy and filter sediment laden flow in channels and on slopes. The logs are flexible to conform to the soil surface and are secured by staking. Aspen Excelsior Sediment Logs can be ordered in custom lengths to meet specific job conditions.

Specifications

Each Aspen Excelsior Log is manufactured under Western Excelsior’s Quality Assurance Program to ensure a continuous distribution of fibers and consistent dimensions. Log dimensions are provided in Table 1 and product characteristics are provided in Table 2. Installation instructions and performance data are available from Western Excelsior’s Technical Support Division.

Log Property	Value	Units
Length	10	ft
Diameter	9, 12, 18 or 20	in
Weight*	25 lbs (9 in) 30 lbs (12 in) 43 lbs (18 in) 50 lbs (20 in)	lbs
Density*	5.8 lbs/ft ³ (9 in) 4.0 lbs/ft ³ (12 in) 3.5 lbs/ft ³ (18 in) 2.4 lbs/ft ³ (20 in)	lbs/ft ³
* Measured at the time of manufacture.		

Fiber Composition	High Altitude Machine Curled Aspen Excelsior
Fiber Dimensions	80% Greater than 6 in.
Netting	0.50" x 0.50" Heavy Duty Synthetic
Configuration	Cylindrical with Closed Ends
End Closure	Hog Ring or Tied