

DESIGN DATA AND TEST RESULTS



EXCEL SR-1™



Specifications

A variety of test methods are utilized to determine performance and conformance values for Rolled Erosion Control Products (RECPs). Information within this document is presented to provide conformance values and recommended design values. Test results obtained for the Excel SR-1 Temporary Erosion Control Blanket (ECB) and general design values are presented in Tables 1-4. For specific information detailing testing protocols, results and application of design values, refer to document number WE_EXCEL_PERF_GEN.

Table 1 - Bench Scale Testing / NTPEP

Test Method	Condition	Result
ASTM D7101 Bench Scale Rainfall and Rainsplash Test	2 in per hour	9.12
	4 in per hour	10.16
	6 in per hour	11.32
ASTM D7207 Bench Scale Shear Resistance Test	1.67 psf (80 PA)	0.5 in (12 mm)
ASTM D7322 Bench Scale Vegetation Establishment Test	Top Soil, Fescue, 21 Day Incubation	424 %

Table 3 - Recommended Design Values*

Design Value	Unvegetated	Vegetated
Typical RUSLE Cover Factor (C Factor)	0.05	N/A
Maximum Slope Gradient (RUSLE)	3H : 1V	N/A
Max Allowable Velocity (0.5 in (12mm) soil loss)	5.0 ft/s (1.5 m/s)	N/A
Max Allowable Shear Stress (0.5 in (12mm) soil loss)	1.6 psf (77 PA)	N/A
CF _{veg} /CF _{TRM}	N/A	N/A

Table 2 - Texas Transportation Institute (TTI) Results

Class	Test Condition	Result
A	< 3H:1 Clay Slope Test	Approved
B	< 3H:1 Sand Slope Test	N/A
C	> 3H:1 Clay Slope Test	Approved
D	> 3H:1 Sand Slope Test	N/A
E	2 psf Partially Vegetated Channel Test	N/A
F	4 psf Partially Vegetated Channel Test	N/A
G	6 psf Partially Vegetated Channel Test	N/A
H	8 psf Partially Vegetated Channel Test	N/A
I	10 psf Partially Vegetated Channel Test	N/A
J	12 psf Partially Vegetated Channel Test	N/A

Table 4 - HEC-15 Resistance to Flow Values

Design Value	Unvegetated
Manning's n @ Tau _{lower} (0.4 psf (19 PA))	0.040
Manning's n @ Tau _{mid} (0.8 psf (38 PA))	0.030
Manning's n @ Tau _{upper} (1.6 psf (77 PA))	0.030

*Recommended Design Values are based on results of standardized industry full-scale testing and may not be applicable for all field conditions. Values provided herein are intended for use with the state of the practice design procedures. For most accurate computation of field performance, consult Excel Erosion Design (EED) at www.westernexcelsior.com.